


TR8500WX-PRO

Wall-Mounted Energy Storage




System Topology



Product-Highlights

Anti-Corrosion & UV Resistance



30% Thinner



8000 Cycles




1C Fast Charging



Intelligent BMS
Multi-Safety Protection



Graphene Technology
High Efficiency



Self-Heating Technology
Work Under -20°C



Multi Functional
Indicator Light



Noise Level < 30dB
Quiet And Comfortable



Product Introduction



Technical Parameter

Model	TR8500WX-PRO
Nominal Voltage	51.2V
Nominal Capacity	314Ah
Charge & Discharge Current	200A
Energy	16.076kWh
Chemistry	LiFePo4
Cycle life	8000 Times 80% SOH (10000 Times 60% SOH)
Rated Output Power	10kW
Certification	CE, UN38.3, RoHS, MSDS
Communication	RS485, Ethernet, CAN
WIFI/BT	Optional
Self-Heating/Fire Extinguishing	Optional
Waterproof	IP66
Noise Level	<30dB
Charge Temperature	0°C to 55°C (32°F to 131°F)
Discharge Temperature	-20°C to 60°C (-4°F to 140°F)
Recommend Operating Temperature	15°C to 35°C (59°F to 95°F)
Storage Temperature	0°C to 35°C (32°F to 95°F)
Altitude	≤3000m
Warranty	10 Years
Dimensions(L×W×H)	75×50×25cm
Weight	~132.5kg



Cleaner Energy, Simplified Life!

SHENZHEN LITTECH ENERGY CO.,LTD

Email: info@lith-tec.com

Add: 14th Floor, Block D, Central Avenue, Xixiang Street, Bao'an District, Shenzhen

©2025 by Shenzhen Littech Energy Co., Ltd. All rights reserved. Specifications and features are subject to change without prior notice. Brand names and logos are trademarks of their respective owners.

CONTACT US:

